

DATE:

PROJECT

COMMENTS:



FEATURES

- NEMA 4X rating
- Ideal for outdoor and wet locations
- Unique, flex arm design allows for up and down and side to side movement
- Rotary locking collar securely locks lens and reflector assembly into place
- Innovative design allows for quick and easy relamping
- Swivel lock secures adjustable head in place
- Designed to fit most standard junction boxes
- Surface mount on wall or ceiling



ORDERING INFORMATION *WRH-GY-1-L65*

1. SERIES	2. HOUSING COLOR	3. HEAD COUNT	4. LAMP SOURCE ¹	5. OPTIONS
WRH	GY GY Gray	1 One Lamp 2 Two Lamps	L65 LED 6V 5W L67 LED 6V 7W L122 LED 12V 2W L125 LED 12V 5W L127 LED 12V 7W L245 LED 24V 5W	BLANK = NO OPTION TP Tamper-proof Screws

ORDERING NOTES

1. Additional lamp options may be available, please contact Quotes@Isolite.com if non-LED lamps are required.

ACCESSORIES; ORDER SEPARATELY

- WG 4 = Wireguard 6.0" X 8.0" X 6.0"

SPECIFICATIONS

CONSTRUCTION

- Durable polycarbonate
- Resilient gasketing enables unit to withstand exposure to moisture and corrosive elements

APPROVALS

- NEMA 4X
- IP66
- Sanitation Listed
- UL924
- NFPA 101 Life Safety Code
- NFPA 70 - NEC
- OSHA

WARRANTY

Isolite offers a 3-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website.